



RENIA – Thinner

Technical Data Sheet 540.000-0814

BASIS:

Mixture of organic solvents. **Free of toluene and MEK.**

MATERIALS:

Can be used to test for Thermoplastic Rubber (TR): put one drop on the plastic material. If it melts and smears, it is TR!

INSTRUCTIONS:

Can be used to thin all Renia contact cements. Also suitable for cleaning glue containers, brushes, and application devices. Can be used to adjust the viscosity of contact cements for mechanical application like rolling or spraying. If mixed thoroughly, no phase separation will take place.

POT-LIFE:

Does not change pot-life of thinned adhesives.

OPEN ASSEMBLY TIME:

Does not change open assembly time of thinned adhesives.

PRESSURE:

Not applicable.

CHARACTERISATION:

Strong solvent with very good penetration/permeation and mixing/thinning abilities.

SHELF-LIFE:

Unlimited at 20 °C

THINNER:

Can be used for thinning.

CLEANING:

Can be used to clean equipment.

LABELLING:

Flashpoint less than 21 °C, highly flammable, Danger

GGVSEB/RID-ADR:	Class 3	Packing Group	: II
IMDG	: 3.2	UN	: 1993
EmS	: F-E, S-D		

PACKAGES:

Number	Package	Net-Contents	Unit per Box
530481	1 ltr can	1 l	21 cans
530485	5 ltr can	5 l	6 cans
530490	12 ltr can	12 l	2 cans